55-5403

Form 113—5M—12-60

Examined 9/6/74 WO
Recorded: B. C. 9/6/74 T. B. WO
Inspection Sheet
Copied 9-9-74 B.M.

REPORT OF WELL DRILLER
STATE OF UTAH

no card

Application No. 43375
~~XXXXXX~~ Area Code 55-5403
Coordinate No. (D-5-4)2 cda

GENERAL STATEMENT: Report of well driller is hereby made and filed with the State Engineer, in accordance with the laws of Utah. (This report shall be filed with the State Engineer within 30 days after the completion or abandonment of the well. Failure to file such reports constitutes a misdemeanor.)

(1) WELL OWNER:
Name R. W. Ripple
Address 5575 No. University Ave., Provo, Ut.

(2) LOCATION OF WELL:
County Wasatch Ground Water Basin (leave blank)
North 955 feet, East 2050 feet from SW Corner
of Section 2, T 5 S, R 4 E SLBM (strike out words not needed)

(3) NATURE OF WORK (check):
New Well XX Replacement Well ☐ Deepening ☐ Repair ☐ Abandon ☐
If abandonment, describe material and procedure:

(4) NATURE OF USE (check):
Domestic ☒ Industrial ☐ Municipal ☐ Stockwater ☒
Irrigation ☐ Mining ☐ Other ☐ Test Well ☐

(5) TYPE OF CONSTRUCTION (check):
Rotary XX Dug ☐ Jetted ☐
Cable ☐ Driven ☐ Bored ☐

(6) CASING SCHEDULE:
Threaded ☐ Welded XX
6 " Diam. from 0 feet to 120 feet Gage std.
4 " Diam. from 115 feet to 150 feet Gage std.
" Diam. from feet to feet Gage
New XX Reject ☐ Used ☐

(7) PERFORATIONS:
Perforated? Yes ☐ No ☐
Type of perforator used
Size of perforations inches by inches
perforations from feet to feet
perforations from feet to feet
perforations from feet to feet
perforations from feet to feet
perforations from feet to feet

(8) SCREENS:
Well screen installed? Yes ☐ No XX
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to
Diam. Slot size Set from ft. to

(9) CONSTRUCTION:
Was well gravel packed? Yes ☐ No XX Size of gravel:
Gravel placed from feet to feet
Was a surface seal provided? Yes XX No ☐
To what depth? 90 feet
Material used in seal: Bentonite & clay cement
Did any strata contain unusable water? Yes ☐ No XX
Type of water: Depth of strata
Method of sealing strata off:
Was surface casing used? Yes ☐ No XX
Was it cemented in place? Yes ☐ No ☐

(10) WATER LEVELS:
Static level 20 feet below land surface Date June 74
Artesian pressure feet above land surface Date

LOG RECEIVED:

(11) FLOWING WELL:
Controlled by (check) Valve ☐
Cap ☐ Plug ☐ No Control ☐
Does well leak around casing? Yes ☐ No ☐

(12) WELL TESTS:
Drawdown is the distance in feet the water level is lowered below static level.
Was a pump test made? Yes ☐ No ☐ If so, by whom?
Yield: gal./min. with feet drawdown after hours
" " " " "
" " " " "
Bailer test apx 45 gal./min. with feet drawdown after hours
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? No ☐ Yes ☐

(13) WELL LOG:
Diameter of well 6 inches
Depth drilled 150 feet. Depth of completed well 150 feet.

NOTE: Place an "X" in the space or combination of spaces needed to designate the material or combination of materials encountered in each depth interval. Under REMARKS make any desirable notes as to occurrence of water and the color, size, nature, etc., of material encountered in each depth interval. Use additional sheet if needed.

DEPTH From	DEPTH To	Clay	Silt	Sand	Gravel	Cobbles	Boulders	Hardpan	Conglomerate	Bedrock	Other	REMARKS
0	20		x									
20	90	x										
90	120	x							x			
120	150									x		

Work started June, 1974 Completed June, 1974

(14) PUMP:
Manufacturer's Name Reda
Type: 19D18P201 H. P. 2
Depth to pump or bowles feet

Well Driller's Statement:
This well was drilled under my supervision, and this report is true to the best of my knowledge and belief.

Name Petersen Bros. Drilling Co., Inc. (Person, firm, or corporation) (Type or print)
Address 1775 No. Beck St., Salt Lake City, Ut.
(Signed) Jay Poulsen (Well Driller)
License No. 249 Date July 18, 1974, 19

USE OTHER SIDE FOR ADDITIONAL REMARKS